

Portable Projector

Vivitek DW275

WXGA projector with a brilliant image, multiple I/O ports and long-life lamp



Features

- Up to 4,000 lumens with a strong contrast ratio
- Native WXGA resolution with a maximum WUXGA resolution
- DLP® and BrilliantColor™ technologies for distinct and vibrant images
- Low cost of ownership and maintenance with an energy efficient lamp for up to 20,000 hours (Long Eco. Mode) of usage
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- Manual zoom and focus for easy adjustment and positioning flexibility
- Full suite of display connectivity inputs and outputs
- 2W of total stereo audio power with multiple audio-in and audio-out ports
- Choose from 8 pre-set display modes to get the most suitable display image
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in standby mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, and security bar

Photos









PRELIMINARY SPECIFICATION FOR REFERENCE ONLY. SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. EXPECTED Q1/2020 PRODUCT LAUNCH.

Specifications

Specifications	
Display Type	Single Chip 0.65" DLP Technology by TI
Brightness	4,000 Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	WUXGA (1,920 x 1,200)
Contrast Ratio	15,000:1
Lamp Life/Type	5,500/7,000/10,000/20,000 Hours (Normal/Eco./Dynamic/Long Eco. Mode), 210W
Throw Ratio	1.55 - 1.86
Image Size (Diagonal)	40" - 300"
Projection Distance	1.3m -10.2m (4.3ft - 33.5ft)
Projection Lens	F=2.42 - 2.62, f=22.5 - 25.79mm
Zoom Ratio	1.2x
Aspect Ratio	16:10
Offset	104%±5%
Keystone Correction	Vertical:±40°
Horizontal Frequency	15 -102kHz
Vertical Frequency	23 - 120Hz
3D Compatibility	Yes
Speaker	2W (Mono)
Computer Compatibility	VGA (640 x 480) to WUXGA_RB(1920 x 1200)
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
I/O Connection Ports	HDMI v1.4b (x2) (HDCP v1.4 Compliant), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (WxDxH)	332 x 244 x 105mm (13" x 9.6" x 4.1")
Weight	2.6kg (5.7lbs)
Available Colors	White
Noise Level	32dB/29dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)
Standard	AC Power Cord, VGA Cable, Remote Control,
Accessories	Documentation Kit
Optional Accessories	Lamp
@202016.44-1. 16.44-1.1 44	and of Dalta Flacturation has Other trademands and the assessment of

©2020 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.







