

ViewSonic® PROJECTOR LS625WP

Key Features

- Laser Phosphor technology
- 20,000 hours lifespan
- Sealed Optical Engine
- 0.52 short throw ratio
- 2,500,000:1 contrast ratio.



Product Description

Featuring WXGA resolution and 3,200 ANSI lumens of brightness, the ViewSonic® LS625WP short throw laser projector is an ideal projection solution for education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, this Lamp Free projector delivers long-term, virtually maintenance-free usage for any classroom. With its 0.52 short throw ratio, H/V keystone and 4 corner adjustment, the LS625WP makes installation more flexible and a hassle-free experience. What's more, the short throw ratio allows you to place the projector just a small distance from a wall or screen to give you a huge image for less cost than a comparably sized display. Crestron, AMX, Extron & Aten, PJLink certification and vController deliver network management capabilities, while exclusive SuperColor™ technology offers a wider colour range for true-to-life images in any classroom.

Visit Us - www.viewsonic.com

SPECIFICATION

Native Resolution:	1280x800
DMD Type:	DC3
Brightness:	3200 ANSI Lumens
Contrast Ratio with SuperEco Mode:	2500000:1
Display Colour:	1.07 Billion Colours
Light Source Type:	Laser Phosphor system
Light Source Life (Normal):	up to 20000
Light Source Life (SuperEco):	up to 20000
Lamp Watt:	Nichia MCD
Lens:	F=2.8, f=7.51mm
Projection Offset:	115.2%+/-5%
Throw Ratio:	0.52
Image Size:	60"~300"
Throw Distance:	0.78m-1.12m (87" @ 0.97m)
Keystone:	H:+/-40° , V:+/-40°
Optical Zoom:	Fixed
Digital Zoom:	0.8x ~ 2.0x
Audible Noise (Normal):	34dB (TBD)
Audible Noise (Eco):	30dB (TBD)
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz
Interactive Camera:	Optional (vTouch-10s)

INPUT

Computer in (share with component):	2
Composite:	1
S-Video:	1
Component (RCAx3):	share w/ Computer in
Audio-in (3.5mm):	1
HDMI:	2 (Back) (HDMI 1.4/ HDCP 1.4) x2

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	10W x 2
USB Type A (Power):	1 (5V/ 1.5A)
12V Trigger (3.5mm):	1 (3.5mm)

CONTROL

RS232 (DB 9-pin male):	1
RJ45:	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 305W Standby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	6.2kg
Dimensions (WxDxH) with Adjustment Foot:	383x291x147mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1 (w/Laser pointer)
QSG:	1
Lens Cover:	Yes

OPTIONAL ACCESSORY